



**Building & DIY Products You Can Trust**

Site 41, Knowsthorpe Way,

Cross Green Industrial Estate, Leeds, LS9 0SW

Telephone: +44 (0) 113 240 3456 Sales: +44 (0) 113 240 2424

Fax: +44 (0) 113 240 0024

e-mail: [info@everbuild.co.uk](mailto:info@everbuild.co.uk)

website: [www.everbuild.co.uk](http://www.everbuild.co.uk)

## CONSTRUCTION PRODUCTS REGULATION

### DECLARATION OF PERFORMANCE

**No: 125/1-CPR/ 2014**

Substrate: Mortar M1

Primer: No primer

1. Identification Code	<b>Everbuild 125 One Hour Caulk</b> <b>Codes: 125C3/C4/BN/MAG</b>
2. Type, Batch and/or Serial Number	<b>- For batch number - see packaging</b>
3. Intended use	<b>Sealant for non-structural use in joints in buildings and pedestrian walkways Part 1: Sealants for Façade elements</b>
4. Manufacturer	<b>Everbuild Building Products Ltd, Site 41, Cross Green Industrial Estate, Knowsthorpe Way, Leeds, LS9 0SW</b>
5. Authorised Representative	<b>Not Applicable</b>
6. Assessment and Verification of Constancy of Performance	<b>System 4</b>
7. Notified Body and Tasks	<b>Not Applicable</b>
8. European Technical Assessment	<b>Not Applicable</b>
9. Declared Performance	<b>TO EN15651-1 (2012)</b>
Type	<b>F INT</b>
Classification	<b>F INT</b>
Reaction to Fire	<b>Class E</b>
Loss of Volume ISO10563	<b>≤45%</b>



Site 41, Knowsthorpe Way,  
Cross Green Industrial Estate, Leeds, LS9 0SW  
Telephone: +44 (0) 113 240 3456 Sales: +44 (0) 113 240 2424  
Fax: +44 (0) 113 240 0024  
e-mail: info@everbuild.co.uk  
website: www.everbuild.co.uk

Resistance to flow ISO7390	≤3 mm
Adhesion/cohesion properties after water immersion (23°C) ISO 10591	≥25%
Durability ISO 8339 and ISO 10591	Pass

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9 . The declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed: I. G. Southerington – Head of Technical P.R. Thomas – Technical Manager

Dated: Leeds, 1/4/14