



## Technical Data Sheet:

<b>Film type:</b>	Polyethylene
<b>Ultimate tensile strength:</b>	PN-EN ISO 527-1-3
longitudinal MPa	18-21
transverse MPa	19-22
<b>Elongation:</b>	PN-EN ISO 527-1-3 (QMP 03)*
longitudinal %	420-450
transverse %	740-780
<b>Adhesive:</b>	Acrylic polymer aqueous dispersion pH 8-9
<b>Peel adhesion:</b>	1,5 +/-0,3 N/cm N/cm (QMP 02)*
<b>Total thickness:</b>	40 +/- 4µ
<b>Application conditions:</b>	
Temperature:	>10 <25°C
Surface:	Free from oils and solvents
<b>Storage:</b>	
Temperature:	>10 <25°C
Humidity:	40-80%
Shelf life:	6 months in above conditions
<b>Permissible deviation:</b>	
Thickness:	PN-C-89258-2
Width:	PN-C-89258-2
<b>Colour:</b>	Transparent Blue, Transparent



## Product data sheet

**Product:** Self-adhesive protective film

**Code:** 2003

**Description:** Surface protection tape which protects interior and exterior windows and glass against paints and dust during house repainting, refurbishing, construction and remodeling.

### Uses:

- Windows and glass.

### Features:

- Easy peel adhesive
- UV resistance: up to 30 days
- Good humidity resistance
- Suitable for all glass and windows
- Environmentally friendly and recyclable