



Technical Data Sheet:

Film type: Polyethylene

Ultimate tensile strength: PN-EN ISO 527-1-3

longitudinal MPa 18-21

transverse MPa 19-22

Elongation: PN-EN ISO 527-1-3 (QMP 03)*

longitudinal % 420-450

transverse % 740-780

Adhesive: Acrylic polymer aqueous dispersion pH 8-9

Peel adhesion: 1,7 +/- 0,3 N/cm N/cm (QMP 02)*

Total thickness: 50 +/- 6µ

Application conditions:

Temperature: >10 <25°C

Surface: Free from oils and solvents

Storage:

Temperature: >10 <25°C

Humidity: 40-80%

Shelf life: 6 months in above conditions

Permissible deviation:

Thickness: PN-C-89258-2

Width: PN-C-89258-2

Colour: Transparent Blue, Transparent



Product data sheet

Product: Self-adhesive protective film

Code: 2004

Description: Surface protection tape which protects interior and exterior windows and glass against paints and dust during house repainting, refurbishing, construction and remodeling.

Uses:

- Windows and glass.

Features:

- Easy peel adhesive
- UV resistance: up to 3 months or up to 6 months
- Good humidity resistance
- Suitable for all glass and windows
- Environmentally friendly and recyclable