

GLOBAL BUT LOCAL PARTNERSHIP

BUILDING TRUST



SikaSeal®-174 Construction

Perimeter sealant for windows and doors



© SIKASERVICES AG / SEALING & BONDING / SIKASEAL-174 CONSTRUCTION / DRG_SIKSERV_000145 / 09.2023

FOR MORE SEALING & BONDING INFORMATION:



Our most current General Sales Conditions shall apply.
Please consult the most current local Product Data Sheet prior to any use.

Sika Services AG

Sealing & Bonding

Tueffenwies 16

CH-8048 Zurich

Switzerland

Phone +41 58 436 40 40

www.sika.com

BUILDING TRUST



SikaSeal®-174 Construction

WEATHER AND MOLD RESISTANT NEUTRAL ALKOXY SILICONE



BENEFITS / CHARACTERISTICS

- Very low VOC emissions
- Very good resistance to UV exposure and weathering
- Very good elasticity and flexibility: $\pm 25\%$
- Non-corrosive, no odor
- Resistant to temperatures between -40°C to $+100^{\circ}\text{C}$

APPROVALS / CERTIFICATES

- GEV Emission Code EC1^{PLUS}
- CE marking: EN 15651-1, EN 15651-2, EN 15651-3

COLORS

Anthracite, ash, black, brown, concrete grey, light grey, transparent, transparent grey, white



WEATHER
RESISTANT



MULTI MATERIAL



SUITABLE FOR
WET ROOMS



USES

- Suitable for perimeter sealing of windows and doors, connection and façade joints
- It contains fungicide to protect the sealant for mold growth in humid areas
- Very good adhesion without a primer on most construction materials and substrates such as glass, ceramic and tiles, clinker, aluminum, steel and wood

EXAMPLES OF USE

- Sealing of window and door frames, windowsills, connection joints between walls and floors, sealing joints in sanitary facilities around bathtubs, toilets or sinks, sealing glass to frame on greenhouses, winter garden and skylights

